



GREE Bora ECO R32

- G10 inverter (min. rotation frequency 15Hz)
- Ionizer (Cold Plasma)
- Capillary tube (for 24 000 btu model: EEV)
- Built-in Wi Fi module
- 4 Fan speeds
- Auto direction of the vertical air flow
- Functions: I Feel (temperature sensor in the remote control), Timer, Auto restart, Warm start, Self-diagnosis, Intelligent Defrost, Force Defrosting, Night mode, Drying of the heat exchanger of the indoor unit in turn-off, Soft start, Lock

R32

WiFi

A++

LOW COOLING
-15°C

LOW HEATING
-15°C

Technical specifications



Model			GWH09AAB-K6DNA4A	GWH12AAB-K6DNA4A	GWH18AAD-K6DNA4B	GWH24AAD-K6DNA4A
Capacity	Cooling	kW	2.5 (0.5 - 3.35)	3.2 (0.6 - 3.6)	4.6 (0.65 - 5.2)	6.15 (1.8 - 6.4)
	Heating	kW	2.8 (0.5 - 3.5)	3.4 (0.6 - 4.4)	5.2 (0.7 - 5.4)	6.45 (1.6 - 6.6)
Power input	Cooling	kW	0.78 (0.16 - 1.4)	0.997 (0.1 - 1.4)	1.43 (0.15 - 1.7)	1.76 (0.6 - 2.5)
	Heating	kW	0.777 (0.2 - 1.5)	0.941 (0.12 - 1.5)	1.4 (0.16 - 1.6)	1.86 (0.65 - 2.6)
Power input	Pdesign (A)	kW	2.6	3.2	3.6	4.7
Seasonal efficiency	Cooling SEER	W/W	6.1	6.1	6.1	6.1
	Heating SCOP	W/W	4.0	4.0	4.0	4.0
Energy class	Cooling		A++	A++	A++	A++
	Heating		A+	A+	A+	A+
Power supply (outdoor unit)			1 Ph / 220-240V / 50Hz			
Current	Cooling	A	3.99	4.5	6.3	7.7
	Heating	A	3.74	4.4	6.2	8.1
	Maximum	A	6.9	7.7	7.5	11.3
Indoor unit	Air flow	m³/h	550 / 500 / 430 / 300	550 / 500 / 430 / 300	850 / 720 / 610 / 520	850 / 720 / 610 / 520
	Sound power level	dB(A)	40 / 37 / 35 / 28	42 / 37 / 35 / 28	48 / 45 / 39 / 34	48 / 44 / 40 / 34
	Dimensions	mm	773 / 250 / 185	773 / 250 / 185	970 / 300 / 225	970 / 300 / 225
	Weight	kg	8.5	8.5	13.5	13.5
Outdoor unit	Air flow	m³/h	1600	2200	2200	3200
	Sound power level	dB(A)	52	52	54	57
	Dimensions	mm	776 / 540 / 320	842 / 596 / 320	842 / 596 / 320	955 / 700 / 396
	Weight	kg	29	31	34	46
Piping connection	Diameter	mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 15.87
	Max. length	m	15	20	20	25
	Max. level difference	m	10	10	10	10
Operation range	Cooling	°C	-15 ~ +43	-15 ~ +43	-15 ~ +43	-15 ~ +43
	Heating	°C	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24